



<b>12 Colorways:</b>	SG24-01 Linen SG24-02 Wheat SG24-03 Sage SG24-04 Jadeite	SG24-05 Greige SG24-06 Pecan SG24-07 Slate SG24-08 Blueberry	SG24-09 Mink SG24-10 Mocha SG24-11 Terracotta SG24-12 Ash
<b>Total Weight</b>	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	<b>Vertical Repeat</b>	N/A
<b>Roll Width</b>	52-54 in. (132-137 cm.)	<b>Horizontal Repeat</b>	N/A
<b>Backing</b>	Woven (Osnaburg)	<b>Nominal Pattern Width</b>	51 in.
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub> (222 x 245 N)	<b>Match Information</b>	Reverse Hang, Random Match
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub> (111 x 111 N)	<b>WA Spec.</b>	WA-101, Type II
<b>Federal Spec.</b>	CCC-W-408D, Type II	<b>ASTM F-793</b>	Category V, Type II
<b>Fire Testing</b>	<p>NFPA 101® Life Safety Code®</p> <p>NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test<sup>1</sup></p> <ul style="list-style-type: none"> <li>- Class A Rating</li> <li>- Flame Spread - 10</li> <li>- Smoke Developed - 5</li> </ul> <p>NFPA 286 Corner Burn Test<sup>2</sup></p> <ul style="list-style-type: none"> <li>- Meets requirements for Flame Spread, Smoke Developed, &amp; Flashover</li> </ul> <p><small>1 When applied to GRC board with A-848-B adhesive    2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive</small></p>		
<b>CE Certification</b>	EU classification in accordance with EN 15102:2007 + A1:2011		
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices		

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
Stacy Garcia New York® and Stacy Garcia® are registered trademarks of Stacy Garcia, Inc.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2023 Koroseal Interior Products, LLC.